

commBOX
Do it better



AVAILABLE IN: 120" - 299" | 2K & 4K

COMMBOX LED BOARD

COMMBOX LED BOARD 16:9

120" | 138" | 150" | 165" | 180" | 220"



CommBox LED Board 16:9 is perfect for boardrooms, meeting rooms, command centres, halls, auditoriums and retail environments. In fact, anywhere a large screen is needed.

KEY FEATURES

- All-in-one fixed sizes 120" – 220".
- Perfect with Microsoft Teams Rooms, Zoom etc.
- Create maximum impact as you deliver your presentation.
- Display single or multiple content at once.
- Display or schedule welcome messages, videos, images, emergency announcements.
- Easy installation - wall mount, hang or mobile stand available.
- Show critical information helping your teams respond quickly and accurately to complex emergency situations.
- Get access to IP cameras and interact with video management systems.

SPECS



3-year on-site swap out warranty with optional 4-5 year



Open cooling design (fan-less) for noiseless performance



Built in audio and external output



Slim design (31mm deep) and narrow bezel



Super bright 550 Nits



High quality display with 2K & 4K resolution



COMMBOX LED BOARD 21:9

132" | 181" | 209"



CommBox LED Board 21:9 is designed for Microsoft Teams Front Row layout. The CommBox LED Board 21:9 provides a truly immersive experience.

KEY FEATURES

- All-in-one fixed sizes 132", 181", 209".
- Perfect with Microsoft Teams Rooms, Zoom etc.
- Create maximum impact as you deliver your presentation.
- Display single or multiple content at once.
- Display or schedule welcome messages, videos, images, emergency announcements.
- Easy installation - wall mount or hang available.
- Show critical information helping your teams respond quickly and accurately to complex emergency situations.
- Get access to IP cameras and interact with video management systems.

SPECS



3-year on-site swap out warranty with optional 4-5 year



Open cooling design (fan-less) for noiseless performance



Built in audio and external output



Slim design (31mm deep) and narrow bezel



Super bright 550 Nits



High quality display

COMMBOX LED BOARD 32:9

199" | 249" | 299"



CommBox LED Board 32:9 is perfect for large meeting spaces where it is critical to see both content and far end participants.

KEY FEATURES

- All-in-one fixed sizes 199", 249", 299".
- Perfect with Microsoft Teams Rooms, Zoom etc.
- Create maximum impact as you deliver your presentation.
- Display single or multiple content at once.
- Display or schedule welcome messages, videos, images, emergency announcements.
- Easy installation - wall mount or hang available.
- Show critical information helping your teams respond quickly and accurately to complex emergency situations.
- Get access to IP cameras and interact with video management systems.

SPECS



3-year on-site swap out warranty with optional 4-5 year



Open cooling design (fan-less) for noiseless performance



Built in audio and external output



Slim design (31mm deep) and narrow bezel



Super bright 550 Nits



High quality display

commBOX

CommBox LED Board 16:9



SPECIFICATIONS

SKU	CBLB12013	CBLB13815	CBLB13819	CBLB15017	CBLB16519	CBLB18020	CBLB22012	CBTL22025
SKU - Impact Resistant	CBLB12013-APL	CBLB13815-APL	CBLB13819-APL	CBLB15017-APL	CBLB16519-APL	CBLB18020-APL	CBLB22012-APL	CBLB22025-APL
Sizes	120"	138"	138"	150"	165"	180"	220"	220"
Pixel Pitch	1.3mm	1.5mm	1.9mm	1.7mm	1.9mm	2mm	1.2mm	2.5mm
Brightness (nits)	100-550	100-550	100-550	100-550	100-550	100-550	100-550	100-550
Panel Resolution	1920 x 1080	1920 x 1080	1600 x 900	1920 x 1080	1920 x 1080	1920 x 1080	3840 x 2160	1920 x 1080
Aspect Ratio	16:9	16:9	16:9	16:9	16:9	16:9	16:9	16:9
Panel Weight	90kg	135kg	135kg	135kg	190kg	190kg	330kg	330kg
Average Power	0.74kw	0.68kw	0.79kw	0.82kw	1.13kw	1.18kw	2.48kw	1.76kw
Power Consumption	1.85kw	1.99kw	1.97kw	2.42kw	2.83kw	3.38kw	6.02kw	5.2kw
LED Lifespan	≥100,000hrs	≥100,000hrs	≥100,000hrs	≥100,000hrs	≥100,000hrs	≥100,000hrs	≥100,000hrs	≥100,000hrs
Service Access	Front	Front	Front	Front	Front	Front	Front	Front
LED Configuration	SMD	SMD	SMD	SMD	SMD	SMD	SMD	SMD
Viewing Angle Horizontal	170°	170°	170°	170°	170°	170°	170°	170°
Viewing Angle Vertical	170°	170°	170°	170°	170°	170°	170°	170°
Viewing Size	2664x1499	3050x1716	3050x1715	3330x1873	3660x2058	3996x2248	4880x2745	4880x2745
Physical Size (mm)	2678x1616x28.5	3064x1832x31	3064x1832x31	3344x1990x28.5	3674x2175x31	4010x2365x28.5	4884x2862x31	4893x2862x31
Cabinets	4x4	5x5	5x5	5x5	6x6	6x6	8x8	8x8
Viewing Distance	2.8m +	3m +	3.6m +	3.3m +	3.6m +	4m +	4m +	2.3m +
Contrast	6500:1	6500:1	6500:1	6500:1	6500:1	6500:1	6500:1	6500:1
Colour Temperature	2300-9300K (adjustable)	2300-9300K (adjustable)	2300-9300K (adjustable)	2300-9300K (adjustable)	2300-9300K (adjustable)	2300-9300K (adjustable)	2300-9300K (adjustable)	2300-9300K (adjustable)

commBOX

CommBox LED Board 16:9



SPECIFICATIONS

SKU	CBLB12013	CBLB13815	CBLB13819	CBLB15017	CBLB16519	CBLB18020	CBLB22012	CBTL22025
SKU - Impact Resistant	CBLB12013-APL	CBLB13815-APL	CBLB13819-APL	CBLB15017-APL	CBLB16519-APL	CBLB18020-APL	CBLB22012-APL	CBLB22025-APL
Frame Material	Magnalium	Magnalium	Magnalium	Magnalium	Magnalium	Magnalium	Magnalium	Magnalium
Installation	Wall, Hanging, Stand	Wall, Hanging, Stand	Wall, Hanging, Stand	Wall, Hanging, Stand	Wall, Hanging, Stand	Wall, Hanging	Wall, Hanging	Wall, Hanging
INPUTS								
HDMI 2.0 Input	3 (2 Internal, 1 External)	3 (2 Internal, 1 External)	3 (2 Internal, 1 External)	3 (2 Internal, 1 External)	3 (2 Internal, 1 External)	3 (2 Internal, 1 External)	3 (2 Internal, 1 External)	3 (2 Internal, 1 External)
HDMI 2.0 Output	1 (Internal)	1 (Internal)	1 (Internal)	1 (Internal)	1 (Internal)	1 (Internal)	1 (Internal)	1 (Internal)
USB 2.0	1 (External)	1 (External)	1 (External)	1 (External)	1 (External)	1 (External)	1 (External)	1 (External)
USB 3.0	1 (External)	1 (External)	1 (External)	1 (External)	1 (External)	1 (External)	1 (External)	1 (External)
Type-C	1 (External)	1 (External)	1 (External)	1 (External)	1 (External)	1 (External)	1 (External)	1 (External)
3.5 Audio Output	2 (1 Internal, 1 External)	2 (1 Internal, 1 External)	2 (1 Internal, 1 External)	2 (1 Internal, 1 External)	2 (1 Internal, 1 External)	2 (1 Internal, 1 External)	2 (1 Internal, 1 External)	2 (1 Internal, 1 External)
Audio Optical Output	1 (Internal)	1 (Internal)	1 (Internal)	1 (Internal)	1 (Internal)	1 (Internal)	1 (Internal)	1 (Internal)
RS232 Port	1 (Internal)	1 (Internal)	1 (Internal)	1 (Internal)	1 (Internal)	1 (Internal)	1 (Internal)	1 (Internal)
RS485 Port	1 (Internal)	1 (Internal)	1 (Internal)	1 (Internal)	1 (Internal)	1 (Internal)	1 (Internal)	1 (Internal)
Bluetooth	1 (Wireless)	1 (Wireless)	1 (Wireless)	1 (Wireless)	1 (Wireless)	1 (Wireless)	1 (Wireless)	1 (Wireless)
LAN	LAN (Internal)	LAN (Internal)	LAN (Internal)	LAN (Internal)	LAN (Internal)	LAN (Internal)	LAN (Internal)	LAN (Internal)
Audio	2 x 30W speakers, 2.0 channel, full frequency range	2 x 30W speakers, 2.0 channel, full frequency range	2 x 30W speakers, 2.0 channel, full frequency range	2 x 30W speakers, 2.0 channel, full frequency range	2 x 30W speakers, 2.0 channel, full frequency range	2 x 30W speakers, 2.0 channel, full frequency range	2 x 30W speakers, 2.0 channel, full frequency range	2 x 30W speakers, 2.0 channel, full frequency range

commBOX

CommBox LED Board 16:9



SPECIFICATIONS

SKU	CBLB12013	CBLB13815	CBLB13819	CBLB15017	CBLB16519	CBLB18020	CBLB22012	CBTL22025
SKU - Impact Resistant	CBLB12013-APL	CBLB13815-APL	CBLB13819-APL	CBLB15017-APL	CBLB16519-APL	CBLB18020-APL	CBLB22012-APL	CBLB22025-APL
Video Processor	Built-in	Built-in	Built-in	Built-in	Built-in	Built-in	Built-in	Built-in
Picture in Picture	HDMI 2.0	HDMI 2.0	HDMI 2.0	HDMI 2.0	HDMI 2.0	HDMI 2.0	HDMI 2.0	HDMI 2.0
Remote Control	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Control via App	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Screen Control	RS232 - IP Control	RS232 - IP Control	RS232 - IP Control	RS232 - IP Control	RS232 - IP Control	RS232 - IP Control	RS232 - IP Control	RS232 - IP Control
Controller	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Wireless Screensharing	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Low Blue Light	Automatic brightness adjustment + 4 different modes	Automatic brightness adjustment + 4 different modes	Automatic brightness adjustment + 4 different modes	Automatic brightness adjustment + 4 different modes	Automatic brightness adjustment + 4 different modes	Automatic brightness adjustment + 4 different modes	Automatic brightness adjustment + 4 different modes	Automatic brightness adjustment + 4 different modes

COMMBBOX EXPERIENCE

Warranty	3 Year Warranty (plus optional 4 or 5 year spare parts warranty)
Support	Same business day help desk support

WHAT'S IN THE BOX

Wall Bracket
Remote Control
Power Cable
Front Maintenance Tool
Tool Kit

commBOX

CommBox LED Board 21:9

SPECIFICATIONS



SKU	CBLB13212	CBLB18115	CBLB20919
SKU - Impact Resistant	CBLB13212-APL	CBLB18115-APL	CBLB20919-APL
Sizes	132"	181"	209"
Pixel Pitch	1.2mm	1.5mm	1.9mm
Brightness (nits)	550	550	550
Panel Resolution	2400x1080	2688x1080	2560x1080
Aspect Ratio	21:9	21:9	21:9
Panel Weight	108kg	189kg	260kg
Average Power (KW)	0.63	0.81	1.01
Power Consumption (KW)	1.84	2.38	2.98
LED Lifespan	≥100,000hrs	≥100,000hrs	≥100,000hrs
Service Access	Front	Front	Front
LED Configuration	SMD	SMD	SMD
Viewing Angle Horizontal	170°	170°	170°
Viewing Angle Vertical	170°	170°	170°
Viewing Size (mm)	3050x1372	4270x1715	4880x2058
Physical Size (mm)	3064x1488x31	4284x1832x31	4894x2175x31
Screen Thickness (mm)	31mm	31mm	31mm
Viewing Distance	≥2.5m	≥3.2m	≥3.8m
Contrast	6500:1	6500:1	6500:1
Colour Temperature	2300-9300K (adjustable)	2300-9300K (adjustable)	2300-9300K (adjustable)
Frame Material	Magnalium	Magnalium	Magnalium
Installation	Wall, Hanging, Stand	Wall, Hanging	Wall, Hanging

commBOX

CommBox LED Board 21:9



SPECIFICATIONS

SKU	CBLB13212	CBLB18115	CBLB20919
SKU - Impact Resistant	CBLB13212-APL	CBLB18115-APL	CBLB20919APL
INPUTS			
HDMI 2.0 Input	3 (2 Internal, 1 External)	3 (2 Internal, 1 External)	3 (2 Internal, 1 External)
HDMI 2.0 Output	1 Internal	1 Internal	1 Internal
USB 2.0	1 External	1 External	1 External
USB 3.0	1 External	1 External	1 External
Type - C	1 External	1 External	1 External
3.5 Audio Output	2 (1 Internal, 1 External)	2 (1 Internal, 1 External)	2 (1 Internal, 1 External)
Audio Optical Output	1 Internal	1 Internal	1 Internal
RS232 Port	1 Internal	1 Internal	1 Internal
RS485 Port	1 Internal	1 Internal	1 Internal
Bluetooth	1 (Wireless)	1 (Wireless)	1 (Wireless)
LAN	1 (Internal)	1 (Internal)	1 (Internal)
Audio	2 x 30W speakers, 2.0 channel, full frequency range	2 x 30W speakers, 2.0 channel, full frequency range	2 x 30W speakers, 2.0 channel, full frequency range

commBOX

CommBox LED Board 21:9




SPECIFICATIONS

SKU	CBLB13212	CBLB18115	CBLB20919
SKU - Impact Resistant	CBLB13212-APL	CBLB18115-APL	CBLB20919-APL
Video Processor	Built-in	Built-in	Built-in
Picture in Picture	HDMI 2.0	HDMI 2.0	HDMI 2.0
Remote Control	Yes	Yes	Yes
Control via App	Yes	Yes	Yes
Screen Control	RS232-IP Control	RS232-IP Control	RS232-IP Control
Controller	Yes	Yes	Yes
Wireless Screensharing	Yes	Yes	Yes
Low Blue Light	Automatic brightness adjustment +4 different modes	Automatic brightness adjustment +4 different modes	Automatic brightness adjustment +4 different modes
COMMBX EXPERIENCE		WHAT'S IN THE BOX	
Warranty	3 Year Warranty (plus optional 4 or 5 year spare parts warranty)		Wall Bracket
Support	Same business day help desk support		Remote Control
			Power Cable
			Front Maintenance Tool
			Tool Kit

 [Request Quote or Demo](#)

commBOX

CommBox LED Board 32:9




SPECIFICATIONS

SKU	CBLB19912	CBLB24915	CBLB29919
SKU - Impact Resistant	CBLB19912-APL	CBLB24915-APL	CBLB29919-APL
Sizes	199"	249"	299"
Pixel Pitch	1.2mm	1.5mm	1.9mm
Brightness (nits)	100-550	100-550	100-550
Panel Resolution	3840x1080	3840x1080	3840x1080
Aspect Ratio	32:9	32:9	32:9
Panel Weight	175kg	265kg	375kg
Average Power (KW)	0.74	1.49	2.26
Power Consumption (KW)	1.85	4.38	5.66
LED Lifespan	≥100,000hrs	≥100,000hrs	≥100,000hrs
Service Access	Front	Front	Front
LED Configuration	SMD	SMD	SMD
Viewing Angle Horizontal	170°	170°	170°
Viewing Angle Vertical	170°	170°	170°
Viewing Size (mm)	4880x1372	6100x1715	7320x2058
Physical Size (mm)	4894x1489x31	6114x1832.31	7334x2175x31
Screen Thickness (mm)	31mm	31mm	31mm
Viewing Distance	≥2.5m	≥2.8m	≥3.8m
Contrast	6500:1	6500:1	6500:1
Colour Temperature	2300-9300K (adjustable)	2300-9300K (adjustable)	2300-9300K (adjustable)
Frame Material	Magnalium	Magnalium	Magnalium
Installation	Wall	Wall	Wall

commBOX

CommBox LED Board 32:9




SPECIFICATIONS

SKU	CBLB19912	CBLB24915	CBLB29919
SKU - Impact Resistant	CBLB19912-APL	CBLB24915-APL	CBLB29919APL
INPUTS			
HDMI 2.0 Input	3 (2 Internal, 1 External)	3 (2 Internal, 1 External)	3 (2 Internal, 1 External)
HDMI 2.0 Output	1 Internal	1 Internal	1 Internal
USB 2.0	1 External	1 External	1 External
USB 3.0	1 External	1 External	1 External
Type - C	1 External	1 External	1 External
3.5 Audio Output	2 (1 Internal, 1 External)	2 (1 Internal, 1 External)	2 (1 Internal, 1 External)
Audio Optical Output	1 Internal	1 Internal	1 Internal
RS232 Port	1 Internal	1 Internal	1 Internal
RS485 Port	1 Internal	1 Internal	1 Internal
Bluetooth	1 (Wireless)	1 (Wireless)	1 (Wireless)
LAN	1 (Internal)	1 (Internal)	1 (Internal)
Audio	2 x 30W speakers, 2.0 channel, full frequency range	2 x 30W speakers, 2.0 channel, full frequency range	2 x 30W speakers, 2.0 channel, full frequency range

commBOX

CommBox LED Board 32:9



SPECIFICATIONS

SKU	CBLB19912	CBLB24915	CBLB29919
SKU - Impact Resistant	CBLB19912-APL	CBLB24915-APL	CBLB29919-APL
Video Processor	Built-in	Built-in	Built-in
Picture in Picture	HDMI 2.0	HDMI 2.0	HDMI 2.0
Remote Control	Yes	Yes	Yes
Control via App	Yes	Yes	Yes
Screen Control	RS232-IP Control	RS232-IP Control	RS232-IP Control
Controller	Yes	Yes	Yes
Wireless Screensharing	Yes	Yes	Yes
Low Blue Light	Automatic brightness adjustment +4 different modes	Automatic brightness adjustment +4 different modes	Automatic brightness adjustment +4 different modes
COMMBX EXPERIENCE		WHAT'S IN THE BOX	
Warranty	3 Year Warranty (plus optional 4 or 5 year spare parts warranty)		Wall Bracket
Support	Same business day help desk support		Remote Control
			Power Cable
			Front Maintenance Tool
			Tool Kit

 [Request Quote or Demo](#)

Do it better

Transforming meeting & learning spaces since 1976.
Australian Designer & Manufacturer of Collaboration Technology.

Click to follow us





commBOX.com.au

commBOX

CommBox Experience Centre

32/6 Jubilee Ave,
Warriewood NSW 2102

 AU +61 2 9975 6001

 sales@commbox.com.au