

commBOX

Classic V3X

SPECIFICATIONS



SKU	CBIC65	CBIC75	CBIC86
LCD Size	65"	75"	86"
Model	Classic V3X 65"	Classic V3X 75"	Classic V3X 86"
DISPLAY			
Tempered Glass	Toughened Glass (Level 7 Mohs) Bonded-zero gap	Toughened Glass (Level 7 Mohs) Bonded-zero gap	Toughened Glass (Level 7 Mohs) Bonded-zero gap
Backlight Type	D-LED	D-LED	D-LED
Resolution	3840 (H) x 2160 (V)	3840 (H) x 2160 (V)	3840 (H) x 2160 (V)
Brightness	350 cd/m2	400 cd/m2	400 cd/m2
Contrast Ratio	1200:1	1200:1	1200:1
Response Time	8ms	8ms	8ms
Pixel Pitch	0.372 x 0.372mm	0.4296 x 0.4296mm	0.4935 x 0.4935mm
Refreshing Frequency	60hz	60hz	60hz
Viewing Angle	178°	178°	178°
Life Time	>30000 hours	>30000 hours	>30000 hours
Colour Gamut	72%	72%	72%
View Area	1428.48 (H) x 803.52 (V)	1649.664(H) x 927.936(V)	1895.04 (H) x 1065.96(V)
Display Colours	1.07B (8bit + FRC)	1.07B (8bit + FRC)	1.07B (8bit + FRC)
Bezel Colours	Black	Black	Black
ELECTRICAL			
CPU - Architecture	ARM A73+A53	ARM A73+A53	ARM A73+A53
CPU - Core	Quad Core	Quad Core	Quad Core
GPU	MaliG51	MaliG51	MaliG51
RAM	3GB DDR	3GB DDR	3GB DDR
ROM	32GB	32GB	32GB
Operating System	CommBox OS powered by Android 8	CommBox OS powered by Android 8	CommBox OS powered by Android 8
Power	240V	240V	240V
Power Consumption without OPS	220W	300W	380W
Stand By	<0.5W	<0.5W	<0.5W
Audio Output Power	2 x 15W	2 x 15W	2 x 15W
Audio Output Power (optional)	15W	15W	15W
OPS Power	DC 18V/5A	DC 18V/5A	DC 18V/5A



Classic V3X

SPECIFICATIONS

SKU	CBIC65	CBIC75	CBIC86
LCD Size	65"	75"	86"
WIFI			
Operating Frequency	2.4GHz/5GHz	2.4GHz/5GHz	2.4GHz/5GHz
WIFI Standard	802.11a/b/g/n/ac	802.11a/b/g/n/ac	802.11a/b/g/n/ac
INPUTS/OUTPUTS			
HDMI In	3	3	3
DP In	1	1	1
VGA In	1	1	1
AV In	1	1	1
YPBPR In	1	1	1
Ops Slot	1	1	1
LAN	2	2	2
Android USB	2	2	2
OPS USB	1	1	1
Public USB	1	1	1
Touch USB	2	2	2
Type C USB	1	1	1
PC Audio In	1	1	1
RS232 In	1	1	1
HDMI Out	1	1	1
AV Out	1	1	1
S/PDIF Out	1	1	1
Audio Out	1	1	1
STRUCTURE			
Product Size	1511.6 x 87.8 x 919.7 mm	1722.5 x 87.1 x 1033.6 mm	1967.9 x 88.7 x 1171.6mm
Package Size	1660 x 220 x 1010 mm	1900 x 225 x 1125 mm	2160 x 225 x 1310 mm
Housing Material	Aluminium/Metal Plate	Aluminium/Metal Plate	Aluminium/Metal Plate
Housing Colour	Black	Black	Black
VESA	4-M8 Screw Hole 600 x 400 mm	4-M8 Screw Hole 800 x 400 mm	4-M8 Screw Hole 800 x 600 mm

commBOX

Classic V3X

SPECIFICATIONS



SKU	CBIC65	CBIC75	CBIC86
LCD Size	65"	75"	86"
INTERACTIVITY			
Sensing Type	Infrared Touch Frame	Infrared Touch Frame	Infrared Touch Frame
Infrared Touch	20 Points	20 Points	20 Points
Resolution	32768 x 32768	32768 x 32768	32768 x 32768
Touch Accuracy	1mm	1mm	1mm
Response Times	<8ms	<8ms	<8ms
Output Mode	HID Standard	HID Standard	HID Standard
Minimum Touch	1.6mm single touch	1.6mm single touch	1.6mm single touch
Object	2mm multiple touch	2mm multiple touch	2mm multiple touch
Platforms Supported	Windows 7 and above Chrome, Mac OS, Linux	Windows 7 and above Chrome, Mac OS, Linux	Windows 7 and above Chrome, Mac OS, Linux

WHAT'S IN THE BOX

Accessories	2 x AAA Batteries 1 x Remote 2 x Stylus with antimicrobial coating 1 x 3M powercord 1 x 3M USB A-B Touch Cable 1 x 3M HDMI Cable 1 x Eraser 1 x Wall Mount Bracket 1 x Instruction Manual 1 x Warranty Card
-------------	--

COMMBOX EXPERIENCE

Warranty	3-Year Warranty
Training	Free online training course for every end-user
Support	Same business day help desk support

PRE-INSTALLED APPLICATIONS

CommBox OS - Homescreen, Sidebar
 CommBox Store
 Airserver
 CommBox Manage - Optional 7 Year Licence
 WPS - Open Office
 CommBox Tools
 CommBox Whiteboard
 Chrome Browser

[Learn more](#)

[Request Quote or Demo](#)